




**Hose Series for Liquids**  
**Barbed Hose and Beaded Hose Flowmeters**  
(TWELVE SIZES 1/4" THRU 3" )



**Outstanding Features**

- ◆ Ideal for use in liquid applications where flowmeter will be installed and fitted to hose or plastic tubing.
- ◆ Sizes 1/4" through 3" available. (Other sizes available, contact factory)
- ◆ Pressure dependent on the hose pressure rating up to 1000 psig. Contact factory for high pressure hose applications.
- ◆ Barbed and beaded hose end connections for permanent applications and applications where installation may be moved from time to time.
- ◆ Multiple pickup coils available.

**General Description**

The Hoffer Hose Series "barbed hose and beaded hose" turbine flowmeters provide extremely accurate flow rate measurement and dependable service for use on liquid applications where the meter must be fitted to hose or connected to plastic tubing. Barbed hose end connections should be selected for permanent installation when the flowmeter is intended to stay once installed. Beaded hose end connections are meant for test installations or applications which are expected to be moved around from time to time. The hose on a beaded end can be readily removed and reinstalled.

# Performance Specifications

**Overrange:** 150% of maximum flow (intermittently).

**Linearity:** ±0.5% of reading (±0.25% typical) over tabulated linear flow range.

**Repeatability:** ±0.1% (±0.05% typical) over tabulated repeatable range.

**Pressure Drop Characteristics:** 4 to 5 PSI at maximum linear flow rate at one CSTK.

**Available Temperature Range:** -450°F to +450°F standard.

**Available Turn Down Range:** 10:1 to 100:1.

**End Fittings:** Barbed Hose and Beaded Hose.

**Materials of Construction:** All 316 stainless steel for long life (with exceptions noted below).

Rotor: 17.4 PH or optional Nickel 200, 430 stainless steel, and others available for media compatibility.

Bearing Styles: 440C stainless steel/ceramic hybrid ball bearings, hard carbon composite, tungsten carbide sleeve, and others available for compatibility with flow media.

## LIQUID SIZE SELECTOR CHART FOR HOSE SERIES TURBINE FLOWMETERS

| Flowmeter Size | MAGNETIC PICKUP COIL  |                    |                           |                        | MODULATED PICKUP COIL |                    |                           |                        |
|----------------|-----------------------|--------------------|---------------------------|------------------------|-----------------------|--------------------|---------------------------|------------------------|
|                | Linear Range (US GPM) | Linear Range (LPM) | Repeatable Range (US GPM) | Repeatable Range (LPM) | Linear Range (US GPM) | Linear Range (LPM) | Repeatable Range (US GPM) | Repeatable Range (LPM) |
| 1/4*           | .35-3.5               | 1.3-13.2           | .25-4.5                   | .95-17                 | .35-3.5               | 1.3-13.2           | .0625-4.5                 | .24-17                 |
| 3/8*           | .75-7.5               | 2.8-28.4           | .3-9                      | 1.1-34                 | .75-7.5               | 2.8-28.4           | .075-9                    | .28-34                 |
| 1/2            | 1.25-9.5              | 4.7-36             | .6-12                     | 2.3-45                 | 1.25-9.5              | 4.7-36             | .12-12                    | .45-45                 |
| 5/8            | 1.75-16               | 6.6-60.6           | .9-20                     | 3.4-75.7               | 1.75-16               | 6.6-60.6           | .2-20                     | .75-75.7               |
| 3/4            | 2.5-29                | 9.5-110            | 1.5-35                    | 5.7-132.5              | 2.5-29                | 9.5-110            | .35-35                    | 1.3-132.5              |
| 1              | 4-60                  | 15-227             | 2-75                      | 7.6-284                | 4-60                  | 15-227             | .75-75                    | 2.8-284                |
| 1-1/4          | 6-93                  | 23-352             | 3-115                     | 11.4-435               | 6-93                  | 23-352             | 1.15-115                  | 4.35-435               |
| 1-1/2          | 8-130                 | 30.3-492           | 5-175                     | 19-662                 | 8-130                 | 30.3-492           | 1.75-175                  | 6.6-662                |
| 2              | 15-225                | 56.8-852           | 11-275                    | 42-1041                | 15-225                | 56.8-852           | 2.75-275                  | 10.4-1041              |
| 2-1/2          | 25-400                | 95-1514            | 15-500                    | 56.8-1893              | 25-400                | 95-1514            | 5-500                     | 19-1893                |
| 3              | 40-650                | 151-2460           | 20-800                    | 76-3028                | 40-650                | 151-2460           | 8-800                     | 30.3-3028              |

NOTE: Performance enhancement techniques are routinely applied to produce larger linear and usable flow ranges. Consult with the applications group at Hoffer with your requirements.

\* The linear flow ranges on 1/4" and 3/8" may be derated depending on bearing selection. Consult applications group for additional information.

## LIQUID TURBINE HOSE SERIES MODEL NUMBERING SYSTEM

MODEL HO(A)X(B)-(C)-(D)-(E)-(F/G/H)-(I)-(J)

PROCESS CONNECTION / END FITTING SIZE AND TURBINE FLOWMETER SIZE

TURBINE FLOWMETER SIZE

MINIMUM FLOW RATE IN GPM

MAXIMUM FLOW RATE IN GPM

BEARING TYPE

PICKUP COILS

COIL SPACING, MECHANICAL DEGREES

RISER AND EXPLOSION PROOF COIL ENCLOSURES

PROCESS CONNECTION/END FITTING HOSE I.D. SIZE AND TYPE

SPECIAL FEATURES

### CALIBRATION

- HO LIQUID TURBINE HOSE SERIES ARE CALIBRATED WITH A 12-POINT ONE CENTISTOKE CALIBRATION WITH THE TOP AND BOTTOM POINTS REPEATED WHICH ARE N.I.S.T. CERTIFIED. VISCOSITY CALIBRATIONS ARE AVAILABLE.
- THE DESIGN PRESSURE WILL HOLD PRESSURE UP TO THE HOSE PRESSURE RATING BEING USED UP TO 1000 PSIG, GREATER PRESSURES ARE AVAILABLE FOR HIGH PRESSURE HOSE APPLICATIONS, PLEASE CONTACT THE FACTORY.
- BARBED HOSE END CONNECTIONS SHOULD BE SELECTED FOR PERMANENT INSTALLATIONS WHEN THE FLOWMETER IS INTENDED TO STAY ONCE INSTALLED.
- BEADED HOSE END CONNECTIONS ARE MEANT FOR TEST INSTALLATIONS OR APPLICATIONS WHICH ARE EXPECTED TO BE MOVED AROUND FROM TIME TO TIME. THE HOSE ON A BEADED END CAN BE READILY REMOVED AND REINSTALLED.

PROCESS CONNECTION/END FITTING SIZE (A) & TURBINE FLOWMETER SIZE (B)

MODEL HO(A)X(B)-(C)-(D)-(E)-(F/G/H)-(I)-(J)

| (A)X(B)    | (A)X(B)    | (A)X(B)                | (A)X(B)      | (A)X(B)      | (A)X(B) |
|------------|------------|------------------------|--------------|--------------|---------|
| HO 1/2X1/4 | HO 1/2X1/2 | HO 3/4X3/4 (Bead Only) | HO 11/4X11/4 | HO 2X2       | HO 3X3  |
| HO 5/8X1/4 | HO 5/8X1/2 | HO 1X3/4               | HO 11/2X11/4 | HO 21/2X2    | HO 4X3  |
| HO 1/2X3/8 | HO 5/8X5/8 | HO 1X1                 | HO 11/2X11/2 | HO 21/2X21/2 |         |
| HO 5/8X3/8 | HO 3/4X5/8 | HO 11/4X1              | HO 2X11/2    | HO 3X21/2    |         |

**MINIMUM FLOW AND MAXIMUM FLOW RATE IN GPM**

MODEL HO( )X( )-(C)-(D)-( )-( / / )-( )-( )

NOTE: FOR EXTENDED RANGES REFER TO SIZE SELECTOR CHARTS.

| TURBINE SIZE | (C)          |    | (D)          |
|--------------|--------------|----|--------------|
|              | MINIMUM FLOW | TO | MAXIMUM FLOW |
| 1/4"         | 35 GPM       |    | 3.5 GPM      |
| 3/8"         | .75 GPM      |    | 7.5 GPM      |
| 1/2"         | 1.25 GPM     |    | 9.5 GPM      |
| 5/8"         | 1.75 GPM     |    | 16 GPM       |
| 3/4"         | 2.5 GPM      |    | 29 GPM       |
| 1"           | 4 GPM        |    | 60 GPM       |
| 1 1/4"       | 6 GPM        |    | 93 GPM       |
| 1 1/2"       | 8 GPM        |    | 130 GPM      |
| 2"           | 15 GPM       |    | 225 GPM      |
| 2 1/2"       | 25 GPM       |    | 400 GPM      |
| 3"           | 40 GPM       |    | 650 GPM      |

**OPTIONAL ACCESSORIES**



**HIT-4U**  
Rate Indicator / Totalizer  
(Refer to HIT-4U Technical Data Sheet)



**Nova-Flow Computer**  
(Refer to Nova Flow Technical Data Sheet)

**BEARING TYPE**

MODEL HO( )X( )-( )-( )-(E)-( / / )-( )-( )

**OPTION (E)**

**1" OR LESS TURBINE SIZES**

- (BP) CERAMIC HYBRID BALL BEARING, SELF LUBRICATING
- (C) HARD CARBON COMPOSITE SLEEVE BEARING
- (T) TUNGSTEN CARBIDE SLEEVE BEARING

**1 1/4" THRU 3" TURBINE SIZES**

- (CB) CERAMIC HYBRID BALL BEARING, SELF LUBRICATING
- (C) HARD CARBON COMPOSITE SLEEVE BEARING
- (T) TUNGSTEN CARBIDE SLEEVE BEARING

**PICKUP COILS**

MODEL HO( )X( )-( )-( )-( )-(F / / )-( )-( )

**OPTION (F)**

|             |                                   |           |  |
|-------------|-----------------------------------|-----------|--|
| (1M)        | ONE MAG COIL                      | (1RPMXXX) | ONE REDI-PULSE MAG COIL (SEE REDI-PULSE AND I.S. REDI-PULSE DATA SHEETS TO COMPLETE REDI-PULSE PART NUMBERS) |
| (2M)        | TWO MAG COILS                     | (2RPMXXX) | TWO REDI-PULSE MAG COILS   |
| (1MC3PA)    | ONE RF COIL                       | (1RPRXXX) | ONE REDI-PULSE RF COIL   |
| (2MC3PA)    | TWO RF COILS                      | (2RPRXXX) | TWO REDI-PULSE RF COILS  |
| (1MC2PAHT)  | ONE HIGH TEMP 6" PIGTAIL RF COIL  | (1DMXXXX) | ONE REDI-PULSE INTRINSICALLY SAFE MAG COIL   |
| (2MC2PAHT)  | TWO HIGH TEMP 6" PIGTAIL RF COILS | (2DMXXXX) | TWO REDI-PULSE INTRINSICALLY SAFE MAG COILS  |
| (1HTM)      | HIGH TEMP MAG COIL                | (1DRXXXX) | ONE REDI-PULSE INTRINSICALLY SAFE RF COIL  |
| (2HTM)      | TWO HIGH TEMP MAG COILS           | (2DRXXXX) | TWO REDI-PULSE INTRINSICALLY SAFE RF COILS   |
| (1ISM)      | ONE INTRINSICALLY SAFE MAG COIL   | (-P*)     | PIGTAIL OR FLYING LEADS, ADD -P AND THE *LENGTH OF LEADS AFTER ANY COIL EXCEPT THE HIGH TEMPERATURE COILS    |
| (2ISM)      | TWO INTRINSICALLY SAFE MAG COILS  |           |  |
| (1ISM-ATEX) | ONE ISM ATEX COIL                 |           |  |
| (2ISM-ATEX) | TWO ISM ATEX COILS                |           |  |

**COIL SPACING, MECHANICAL DEGREES**

MODEL HO( )X( )-( )-( )-( )-( / G / )-( )-( )

NOTE (G): 90 DEGREE ELECTRICAL COIL SPACING FOR TWO COILS REQUIRE THE FOLLOWING MECHANICAL SPACING:

| TURBINE SIZE | FORWARD MECH. DEGREES | REVERSE DEGREES MECH. DEGREES | COIL SPARE DEGREES |
|--------------|-----------------------|-------------------------------|--------------------|
| 1/4"         | ZERO                  | 135                           | 250                |
| 3/8"         | ZERO                  | 135                           | 250                |
| 1/2"         | ZERO                  | 135                           | 250                |
| 5/8"         | ZERO                  | 135                           | 180                |
| 3/4"         | ZERO                  | 135                           | 250                |
| 1"           | ZERO                  | 135                           | 250                |
| 1 1/4"       | ZERO                  | 135                           | 250                |
| 1 1/2"       | ZERO                  | 135                           | 250                |
| 2"           | ZERO                  | 101.25                        | 250                |
| 2 1/2"       | ZERO                  | 97.50                         | 180                |
| 3"           | ZERO                  | 97.50                         | 180                |

**RISER AND EXPLOSION PROOF COIL ENCLOSURES**

MODEL HO( )X( )-( )-( )-( )-( / / H )-( )-( )

**OPTION ( H )**

- (X) 1" MNPT RISER, WELDED TO BODY, REQUIRED FOR ALL TYPE OF ENCLOSURES.
- (X-ATEX) 3/4" MALE NPT COIL RISER-ATEX EXD COMPLIANT.
- (XE2) 1" MNPT RISER WITH E2 ENCLOSURE. (SEE CHART)\*
- (X-ATEX)E2 3/4" MNPT RISER WITH E2 ENCLOSURE. (SEE CHART)\*
- (X8S) 8" LONG S/S 1" MNPT RISER. (FOR FLUID TEMPERATURES BELOW -40°F (-40°C) OR ABOVE +140°F +60°C).
- (X8S-ATEX) 8" LONG S/S 3/4" MNPT RISER. (FOR FLUID TEMPERATURES BELOW -40°F (-40°C) OR ABOVE +140°F +60°C).

|   |   |
|---|---|
| <b>*E2 EXPLOSION-PROOF/FLAME-PROOF ENCLOSURE WITH 3/4" FNPT MOUNT AND 3/4" CABLE ENTRY RATINGS:</b> |   |
| FM:   | CLASS I, DIV. 1, GR. ABCD, CLASS II/III, DIV. 1, GR. EFG, TYPE 4X   |
| CSA:  | CLASS I, DIV. 1, GR. ABCD, CLASS II, DIV. 1, GR. EFG, CLASS III, TYPE 4X EX D IIC, CLASS I, ZONE 1, IP 66 |
| ATEX:   | EX II 2GD Ex d tD IIC, IP66/68  |
| IEC:  | EX D IIC IP68   |

**PROCESS CONNECTION/END FITTING HOSE I.D. AND TYPE**

MODEL HO( )X( )-( )-( )-( )-( / / )-( )-( J )

**OPTION ( I )**

| <b>End Fitting Size and Type</b> |                      |                        |
|----------------------------------|----------------------|------------------------|
| <b>Reference Turbine Size</b>    | <b>Hose I.D.</b>     | <b>(I) Select Type</b> |
| 1/4                              | for 1/2" I.D. hose   | 1/2bead or 1/2barb     |
| 1/4                              | for 5/8" I.D. hose   | 5/8bead or 5/8barb     |
| 3/8                              | for 1/2" I.D. hose   | 1/2bead or 1/2barb     |
| 3/8                              | for 5/8" I.D. hose   | 5/8bead or 5/8barb     |
| 1/2                              | for 1/2" I.D. hose   | 1/2bead or 1/2barb     |
| 1/2                              | for 5/8" I.D. hose   | 5/8bead or 5/8barb     |
| 5/8                              | for 5/8" I.D. hose   | 5/8bead or 5/8barb     |
| 5/8                              | for 3/4" I.D. hose   | 3/4bead ONLY           |
| 3/4                              | for 3/4" I.D. hose   | 3/4bead or 3/4barb     |
| 3/4                              | for 1" I.D. hose     | 1bead or 1barb         |
| 1                                | for 1" I.D. hose     | 1bead or 1barb         |
| 1                                | for 1 1/4" I.D. hose | 1 1/4bead or 1 1/4barb |
| 1 1/4                            | for 1 1/4" I.D. hose | 1 1/4bead or 1 1/4barb |
| 1 1/4                            | for 1 1/2" I.D. hose | 1 1/2bead or 1 1/2barb |
| 1 1/2                            | for 1 1/2" I.D. hose | 1 1/2bead or 1 1/2barb |
| 1 1/2                            | for 2" I.D. hose     | 2bead or 2barb         |
| 2                                | for 2" I.D. hose     | 2bead or 2barb         |
| 2                                | for 2 1/2" I.D. hose | 2 1/2bead or 2 1/2barb |
| 2 1/2                            | for 2 1/2" I.D. hose | 2 1/2bead or 2 1/2barb |
| 2 1/2                            | for 3" I.D. hose     | 3bead or 3barb         |
| 3                                | for 3" I.D. hose     | 3bead or 3barb         |
| 3                                | for 4" I.D. hose     | 4bead or 4barb         |

**Note:** Pressure is rated to 1000 PSIG or to the rating of the hose. Higher pressures for high pressure hose and other size hose I.D.'s are available upon request.

**SPECIAL FEATURES**

MODEL HO( )X( )-( )-( )-( )-( / / )-( )-( J )

**OPTION ( J )**

**SPECIAL FEATURES**

- (CE) CE MARK REQUIRED FOR EUROPE
- (PED-CE) PED-CE MARK REQUIRED FOR EUROPE
- (SEP-CE) SOUND ENGINEERING PRACTICE
- (SP) ANY SPECIAL FEATURES THAT ARE NOT COVERED IN THE MODEL NUMBER, USE A WRITTEN DESCRIPTION OF THE -SP.
- (X) NO SPECIAL FEATURES



**HOFFER FLOW CONTROLS, INC.**  
 107 Kitty Hawk Lane, P. O. Box 2145, Elizabeth City, NC 27906-2145  
 800-628-4584 252-331-1997 FAX 252-331-2886  
 www.hofferflow.com email: info@hofferflow.com

*The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.*



Hoffer Flow Controls Quality Management System



Certified to ISO 9001:2015



Precisely Right.